



ALUMINUM COMPLEX GREASE SYNTHETIC

Aluminum Complex grease is a high-performance, synthetic product developed for use in the food processing industry. It is based on synthetic base oil with Aluminum complex thickener and performance additives. This grease has a strong affinity for metal and it is highly stable when operating with heavy loads at high temperatures. It also has excellent sealing properties and it is ideal for lubricating bearings subjected to high temperatures and pressures.

APPLICATIONS

Aluminum Complex grease is used in bearings that operate at high temperatures, bearings in refrigeration facilities, bearings that require a lubricant with excellent adhesive and sealing properties.

PRODUCT ADVANTAGES

- The operating temperature range is -40°C to 180°C
- Operates at extreme temperatures
- Excellent load-carrying capacity
- Good resistance against water
- Excellent adhesive and sealing properties
- Long-lasting lubrication

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
NLGI Grade	-	1	2
Thickener Type	-	Al-Complex Thickener	Al-Complex Thickener
Base Oil Type	-	Synthetic	Synthetic
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Ivory	Ivory
Work Penetration @25°C	ASTM D217	310-340	265-295
Dropping Point °C, Min	ASTM D2265	250	250
Four Ball Weld Load, Kgf, Min	ASTM D2596	250	250
Operating Temperature Range °C	INTERNAL	-40 to 180	
Base Oil Viscosity @40°C (Cst)	ASTM D445	100	100

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease and grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. For further information on Safety Guidelines please refer to MSDS available on our website www.rexol.uk

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet at www.rexol.uk

PROTECT THE ENVIRONMENT:

Comply with local regulations. Do not discharge into drains, soil, or water.

STORAGE & HANDLING:

We recommend storing all packages under cover. Never leave grease containers improperly covered, uncovered, or open. Keep them tightly sealed between uses. If the containers are stored outside, a heavy canvas tarpaulin, plastic sheet, or lean-to can be used to keep off water or dirt. Ideally, grease should be stored in a cool, dry indoor area that does not exceed 86 degrees °F (30 degrees °C) and remains above 32 degrees °F (°C).