



BENTONITE GREASE

Bentonite grease is made from Bentonite clay, highly refined heavy base oil, anti-oxidant and anti-rust additives. It is resistant to water.

APPLICATIONS

Bentonite grease is suitable for use within a very wide temperature range and especially at elevated temperatures for both industrial and automotive applications. The all-round properties make it suitable for various types of bearings, including temperature peaks up to 160°C.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 160°C
- Non-melting thickener keeps consistency at high temperature
- Good water resistance properties
- Good oxidation and thermal stability
- Suitable for heavy and shock loading capabilities
- Good corrosion and rust protection

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	-	2
Thickener Type	-	Bentone Clay
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	Brown
Work Penetration @25°C	ASTM D217	265-295
Dropping Point °C, Min	ASTM D2265	Non drop
Operating Temperature Range °C	INTERNAL	-20 to 160
Base Oil Viscosity @40°C (Cst)	ASTM D445	460

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease and grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. For further information on Safety Guidelines please refer to MSDS available on our website www.rexol.uk

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet at www.rexol.uk

PROTECT THE ENVIRONMENT:

Comply with local regulations. Do not discharge into drains, soil, or water.

STORAGE & HANDLING:

We recommend storing all packages under cover. Never leave grease containers improperly covered, uncovered, or open. Keep them tightly sealed between uses. If the containers are stored outside, a heavy canvas tarpaulin, plastic sheet, or lean-to can be used to keep off water or dirt. Ideally, grease should be stored in a cool, dry indoor area that does not exceed 86 degrees °F (30 degrees °C) and remains above 32 degrees °F (°C).