



CALCIUM SULFONATE COMPLEX GREASE

Calcium Sulfonate Complex is a high-performance, heavy-duty lubricating grease based on calcium sulfonate complex thickener system and high-quality heavy mineral base oil. A unique structure of calcium sulfonate complex thickener provides high dropping point, extraordinary extreme-pressure and anti-wear performances, excellent rust protection, superior mechanical stability and superior resistance against water washout.

APPLICATIONS

Calcium Sulfonate Complex grease is used in industrial equipment operating under unfavorable conditions involving water contamination, high loads and/or high temperatures, plain and rolling element bearings operating in corrosive environmental conditions, rolling mills, hot roll cables, continuous casters, ingot buggies and slab mills, steel mill roller bearings, conveyors and gears, marine and heavy mobile equipment exposed to salt water, paper machine wet- and dry-end bearings and hot calendar stacks, automotive wheel bearings and chassis parts.

PRODUCT ADVANTAGES

- The operating temperature range is from -25 to 180°C
- High-load carrying capacity
- Good water resistance properties
- Good oxidation and thermal stability
- Good mechanical stability
- Good rust and corrosion protection
- Excellent EP and anti-wear properties

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
NLGI Grade	-	15	2
Thickener Type	-	Calcium Sulfonate Complex	
Appearance	Visual	Smooth & Homogeneous	
Color	Visual	Brown	
Work Penetration @25°C	ASTM D217	305	265-295
Copper Strip Corrosion For 24hrs @100 °C	ASTM D4048	1b	
Dropping Point °C, Min	ASTM D2265	260	260
Water Washout Resistance %Wt. @79°C	ASTM D1264	0.3	
Four Ball Weld Load, Kgf, Min	ASTM D2596	500	
Four Ball, Wear Scar, dia, mm	ASTM D2266	max 0.6	
Operating Temperature Range °C	INTERNAL	-25 to 180	
Base Oil Viscosity @40°C (Cst)	ASTM D445	460	460

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease and grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. For further information on Safety Guidelines please refer to MSDS available on our website www.rexol.uk

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet at www.rexol.uk

PROTECT THE ENVIRONMENT:

Comply with local regulations. Do not discharge into drains, soil, or water.

STORAGE & HANDLING:

We recommend storing all packages under cover. Never leave grease containers improperly covered, uncovered, or open. Keep them tightly sealed between uses. If the containers are stored outside, a heavy canvas tarpaulin, plastic sheet, or lean-to can be used to keep off water or dirt. Ideally, grease should be stored in a cool, dry indoor area that does not exceed 86 degrees °F (30 degrees °C) and remains above 32 degrees °F (°C).