



LITHIUM COMPLEX EP 220 GREASE

Lithium Complex EP grease is made from high viscosity index mineral oils and performance additives to enhance extreme pressure, anti-wear, anti-corrosion and anti-oxidation properties. This grease is recommended for bearings operating under the load at high temperatures. This product is also suitable for use in applications such as continuous casting, quarries, breakers, roller conveyors and automotive wheel bearings.

APPLICATIONS

Lithium Complex EP is recommended for bearings operating under the load at high temperatures. It is also suitable for use in applications such as continuous casting, quarries, breakers, roller conveyors and automotive wheel bearings.

PRODUCT ADVANTAGES

- The operating temperature range is from -25°C to 140°C
- Excellent mechanical stability under vibrating conditions
- Excellent extreme pressure properties
- Excellent wear resistance
- High dropping point
- Good corrosion protection

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE		
		1	2	3
NLGI Grade	-	1	2	3
Thickener Type	-	Lithium complex	Lithium complex	Lithium complex
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Blue / Red / Natural		
Work Penetration @25°C	ASTM D217	310-340	265 - 295	220 - 250
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b max	1b max	1b max
Dropping Point °C, Min	ASTM D2265	240	240	240
Water Washout Resistance %Wt @79°C	ASTM D1264	max 5	max 5	max 5
Four Ball, Load Wear Scar, Mm	ASTM D2266	0.6	0.6	0.6
Four Ball Weld Load, Kg, Min	ASTM D2596	min 250	min 250	min 250
Wheel Bearing Leakage After 6hrs @ 105°C, gm	ASTM D1263	max 8	max 8	max 8
Oil Separation, % 30hrs @100°C	ASTM D6184	max 5	max 5	max 5
Operating Temperature Range, °C	INTERNAL	-25 to 140		
Base Oil Viscosity @40°C (Cst)	ASTM 445	220	220	220

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease and grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. For further information on Safety Guidelines please refer to MSDS available on our website www.rexol.uk

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet at www.rexol.uk

PROTECT THE ENVIRONMENT:

Comply with local regulations. Do not discharge into drains, soil, or water.

STORAGE & HANDLING:

We recommend storing all packages under cover. Never leave grease containers improperly covered, uncovered, or open. Keep them tightly sealed between uses. If the containers are stored outside, a heavy canvas tarpaulin, plastic sheet, or lean-to can be used to keep off water or dirt. Ideally, grease should be stored in a cool, dry indoor area that does not exceed 86 degrees °F (30 degrees °C) and remains above 32 degrees °F (°C).